

Analysis of Algorithms

Data Structures and Algorithms for Computational Linguistics III
(ISCL-BA-07)Çağrı Çöltekin
ccoltekin@ifa.uni-tuebingen.deUniversity of Tübingen
Seminar für Sprachwissenschaft

Winter Semester 2025/26

version: 1/23/24 10:22:27

What are we analyzing?

- So far, we frequently asked: 'can we do better?'
- Now, we turn to the questions of
 - what is better?
 - how do we know an algorithm is better than the other?
- There are many properties that we may want to improve
 - correctness
 - robustness
 - simplicity
 - ...
 - In this lecture, *efficiency* will be our focus
 - in particular time efficiency/complexity

C. Çöltekin, ISL / University of Tübingen

Winter Semester 2025/26 1 / 31

Introduction Performance Asymptotic analysis

How to determine running time of an algorithm?

write the code, experiment

- A possible approach:
 - Implement the algorithm
 - Test with varying input
 - Analyze the results
- A few issues with this approach:
 - Implementing something that does not work is not productive (or fun)
 - It is often not possible to cover all potential inputs
 - If your version takes 10 seconds less than a version reported 10 years ago, do you really have an improvement?
- A formal approach offers some help here

C. Çöltekin, ISL / University of Tübingen

Winter Semester 2025/26 2 / 31

Introduction Performance Asymptotic analysis

Some functions to know about

Family	Definition
Constant	$f(n) = c$
Logarithmic	$f(n) = \log_b n$
Linear	$f(n) = n$
$N \log N$	$f(n) = n \log n$
Quadratic	$f(n) = n^2$
Cubic	$f(n) = n^3$
Other polynomials	$f(n) = n^k$, for $k > 3$
Exponential	$f(n) = b^n$, for $b > 1$
Factorial	$f(n) = n!$

- We will use these functions to characterize running times of algorithms


C. Çöltekin, ISL / University of Tübingen

Winter Semester 2025/26 3 / 31

Introduction Performance Asymptotic analysis

Some functions to know about

the picture - why we care about their difference




C. Çöltekin, ISL / University of Tübingen

Winter Semester 2025/26 4 / 31

Introduction Performance Asymptotic analysis

Some functions to know about

the bigger picture



C. Çöltekin, ISL / University of Tübingen

Winter Semester 2025/26 5 / 31

Introduction Performance Asymptotic analysis

A few facts about logarithms

- Logarithm is the inverse of exponentiation:

$$x = \log_b n \iff b^x = n$$
- We will mostly use base-2 logarithms. For us, no-base means base-2
- Additional properties:

$$\begin{aligned} \log xy &= \log x + \log y \\ \log \frac{x}{y} &= \log x - \log y \\ \log x^a &= a \log x \\ \log_b x &= \frac{\log_a x}{\log_a b} \end{aligned}$$

- Logarithmic functions grow (much) slower than linear functions

C. Çöltekin, ISL / University of Tübingen

Winter Semester 2025/26 6 / 31

Introduction Performance Asymptotic analysis

Polynomials

- A degree-0 polynomial is a constant function ($f(n) = c$)
- Degree-1 is linear ($f(n) = n + c$)
- Degree-2 is quadratic ($f(n) = n^2 + n + c$)
- ...
- We generally drop the lower order terms (soon we'll see why)
- Sometimes it will be useful to remember that

$$1 + 2 + 3 + \dots + n = \frac{n(n+1)}{2}$$

C. Çöltekin, ISL / University of Tübingen

Winter Semester 2025/26 7 / 31

Introduction Performance Asymptotic analysis

Combinations and permutations

- $n! = n \times (n-1) \times \dots \times 2 \times 1$
- Permutations:

$$P(n, k) = n \times (n-1) \times \dots \times (n-k+1) = \frac{n!}{(n-k)!}$$

- Combinations 'n choose k':

$$C(n, k) = \binom{n}{k} = \frac{P(n, k)}{P(k, k)} = \frac{n!}{(n-k)! \times k!}$$

C. Çöltekin, ISL / University of Tübingen

Winter Semester 2025/26 8 / 31

Introduction Performance Asymptotic analysis

Proof by induction

- Induction is an important proof technique
- It is often used for both proving the correctness and running times of algorithms
- It works if we can enumerate the steps of an algorithm (loops, recursion)
 - Show that base case holds
 - Assume the result is correct for n , show that it also holds for $n+1$

C. Çöltekin, ISL / University of Tübingen

Winter Semester 2025/26 9 / 31

Introduction Performance Asymptotic analysis

Proof by induction

Example: show that $1 + 2 + 3 + \dots + n = n(n+1)/2$

- Base case, for $n=1$

$$(1 \times 2)/2 = 1$$

- Assuming

$$\sum_{i=1}^n i = \frac{n(n+1)}{2}$$

we need to show that

$$\begin{aligned} \sum_{i=1}^{n+1} i &= \frac{(n+1)(n+2)}{2} \\ \frac{n(n+1)}{2} + (n+1) &= \frac{n(n+1) + 2(n+1)}{2} = \frac{(n+1)(n+2)}{2} \end{aligned}$$

C. Çöltekin, ISL / University of Tübingen

Winter Semester 2025/26 10 / 31

Introduction Performance Asymptotic analysis

Formal analysis of running time of algorithms

- We are focusing on characterizing running time of algorithms
- The running time is characterized as a function of input size
- We are aiming for an analysis method
 - independent of hardware / software environment
 - does not require implementation before analysis
 - considers all possible inputs

C. Çöltekin, ISL / University of Tübingen


Winter Semester 2025/26 11 / 31

How much hardware independence?

quite, but not completely: we assume a RAM model of computing

- Characterized by random access memory (RAM) (e.g., in comparison to a sequential memory, like a tape)
- We assume the system can perform some primitive operations (addition, comparison) in constant time
- The data and the instructions are stored in the RAM
- The processor fetches them as needed, and executes following the instructions
- This is mostly true for any computing system we use in practice

RAM model: an example



- Processing unit performs basic operations in constant time
- Any memory cell with an address can be accessed in equal (constant) time
- The instructions as well as the data is kept in the memory
- There may be other, specialized registers
- Modern processing units also employ a 'cache'

Formal analysis of running time

- Simply count the number of *primitive operations*
- Primitive operations include:
 - Assignment
 - Arithmetic operations
 - Comparing primitive data types (e.g., numbers)
 - Accessing a single memory location
 - Function calls, return from functions
- Not** primitive operations:
 - loops, recursion
 - comparing sequences

Focus on the worst case

- Algorithms are generally faster on certain input than others
- In most cases, we are interested in the *worst case analysis*
 - Guaranteeing worst case is important
 - It is also relatively easier: we need to identify the worst-case input
- Average case analysis is also useful, but
 - requires defining a distribution over possible inputs
 - often more challenging

Counting primitive operations

example: nearest points, the naive algorithm

```
def shortest_distance(points):
    n = len(points)           # 2 (constant)
    min = float('inf')        # 1 (constant)
    for i in range(n):         # n times
        for j in range(i):     # 29 (constant)
            d = distance(points[i], points[j]) # 1 (constant)
            if d < min:         # 1 (constant)
                min = d        # 1 (constant)
    return min                # 1 (constant)
```

$$T(n) = 3 + (1 + 2 + 3 + \dots + n - 1) \times 4 + 1$$

$$= 4 \times \frac{(n-1)n}{2} + 4$$

Big-O notation


- Big-O notation is used for indicating an upper bound on running time of an algorithm as a function of running time
- If running time of an algorithm is $O(f(n))$, its running time grows proportional to $f(n)$ as the input size n grows
- More formally, given functions $f(n)$ and $g(n)$, we say that $f(n)$ is $O(g(n))$ if there is a constant $c > 0$ and integer $n_0 \geq 1$ such that

$$f(n) \leq c \times g(n) \text{ for } n \geq n_0$$

- Sometimes the notation $f(n) = O(g(n))$ is also used, but beware: this equal sign is not symmetric


Big-O example

$T(n) = n^2 - 2n + 5$ is $O(n^2)$




Big-O, another example

$T(n) = n^2 + 3n$ is $O(n^2)$



Big-O, yet another example

but n^2 is not $O(n)$ – proof by picture



Back to the function classes

Family	Definition
Constant	$f(n) = c$
Logarithmic	$f(n) = \log_b n$
Linear	$f(n) = n$
N log N	$f(n) = n \log n$
Quadratic	$f(n) = n^2$
Cubic	$f(n) = n^3$
Other polynomials	$f(n) = n^k$, for $k > 3$
Exponential	$f(n) = b^n$, for $b > 1$
Factorial	$f(n) = n!$

- None of these functions can be expressed as a constant factor of another

Rules of thumb

Drop the lower order terms

- In the big-O notation, we drop the constants and lower order terms
 - Any polynomial degree d is $O(n^d)$
 - $10n^3 + 4n^2 + n + 100$ is $O(n^3)$
 - Drop any lower order terms:
 - $2^n + 10n^3$ is $O(2^n)$
- Use the tight but simpler bounds:
 - $5n + 100$ is $O(5n)$, but we prefer $O(n)$
 - $4n^2 + n + 100$ is $O(n^2)$, but we prefer $O(n^2)$
- Transitivity: if $f(n) = O(g(n))$, and $g(n) = O(h(n))$, then $f(n) = O(h(n))$
- Additivity: if both $f(n)$ and $g(n)$ are $O(h(n))$ then $f(n) + g(n)$ is $O(h(n))$

Rules of thumb

examples

$f(n)$	$O(f(n))$
$7n - 2$	n
$3n^3 - 2n^2 + 5$	n^3
$3 \log n + 5$	$\log n$
$\log n + 2^n$	2^n
$10n^3 + 2^n$	2^n
$\log 2^n$	n
$2^n + 4^n$	4^n
100×2^n	2^n
$n2^n$	$n2^n$
$\log n!$	$n \log n$

Big-O: back to nearest points

```
def shortest_distance(points):
    n = len(points)
    min = 0
    for i in range(n):
        for j in range(i):
            d = distance(points[i], points[j])
            if min > d:
                min = d
    return min
```

2 (constant?)
1 (constant)
n times
n times
2? (constant)
1 (constant)
1 (constant)

$$T(n) = 3 + (1 + 2 + 3 + \dots + n - 1) \times 4 + 1$$

$$= 4 \times \frac{(n-1)n}{2} + 4 - 2n^2 - 2n + 4$$

$$= O(n^2)$$

Recursive example

Recursive binary search

```
def rbs(a, x, L=0, R=n):
    if L >= R:
        return None
    M = (L + R) // 2
    if a[M] == x:
        return M
    if a[M] > x:
        return rbs(a, x, L, M-1)
    else:
        return rbs(a, x, M+1, R)
```

- Counting is not easy, but realize that $T(n) = c + T(n/2)$
- This is a recursive formula, it means $T(n/2) = c + T(n/4)$, $T(n/4) = c + T(n/8)$, ...
- So, $T(n) = 2c + T(n/4) = 3c + T(n/8)$
- More generally, $T(n) = lc + T(n/2^l)$
- Recursion terminates when $n/2^l = 1$, or $n = 2^l$, the good news: $l = \log n$
- $T(n) = c \log n + T(1) = O(\log n)$


You do not always need to prove: for most recurrence relations, there is a way to obtain quick solutions (we are not going to cover it further, see Appendix)

Worst case and asymptotic analysis

pros and cons

- We typically compare algorithms based on their worst-case performance
 - pro it is easier, and we get a (very) strong guarantee: we know that the algorithm won't perform worse than the bound
 - con a (very) strong guarantee: in some (many?) problems, worst case examples are rare
 - In practice you may prefer an algorithm that does better on average (we'll see examples from sorting)
- Our analyses are based on asymptotic behavior
 - pro for a 'large enough' input, asymptotic analysis is correct
 - con constant or lower order factors are not always unimportant
 - A constant factor of 100^{100} should probably not be ignored

Big-O, Big-Ω, Big-Θ: an example

 $T(n) = n^2 + 3n$ is $\Theta(n^2)$ 

- \square for $c = 2$ and $n_0 = 3$
 $T(n) \leq cg(n)$ for $n > n_0$
- \square for $c = 1$ and $n_0 = 0$
 $T(n) \geq cg(n)$ for $n > n_0$
- \square for $c = 2$, $n_0 = 3$, $c' = 1$ and $n'_0 = 0$
 $T(n) \leq cg(n)$ for $n > n_0$ and
 $T(n) \geq c'g(n)$ for $n > n'_0$

Acknowledgments, credits, references

- Goodrich, Michael T., Roberto Tamassia, and Michael H. Goldwasser (2013). *Data Structures and Algorithms in Python*. John Wiley & Sons, Incorporated. isbn: 9781118476734.

Exercise

Sort the functions based on asymptotic order of growth

$\log n^{1000}$
 $n \log(n)$
 5^n
 $\log n$
 $\log n^{1/\log n}$
 $\log n$
 $\log 2^n/n$
 $\log n!$
 $\log 2^n$

$\log n^n$
 $\left(\frac{n}{2}\right)$
 $\log \log n!$
 \sqrt{n}
 n^2
 2^n
 $\left(\frac{n}{2}\right)$

Big-O examples

Linear search

```
def linear_search(seq, val):
    i, m = 0, len(seq)
    while i < m:
        if seq[i] == val:
            return i
        i = i + 1
    return None
```

- What is the worst-case running time?
 - 2 assignments
 - 2n comparisons, n increment
 - 1 return statement $T(n) = 3n + 3 = O(n)$
- What is the average-case running time?
 - 2 assignments
 - 2(n/2) comparisons, n/2 increment, 1 return $T(n) = 3/2n + 3 = O(n)$
- What about best case? $O(1)$

Note: do not confuse the big-O with the worst case analysis.

Why asymptotic analysis is important?

'maximum problem size'

- Assume we can solve a problem of size m in a given time on current hardware
- We get a better computer, which runs 1024 times faster
- New problem size we can solve in the same time

Complexity	new problem size
Linear (n)	1024m
Quadratic (n^2)	32m
Exponential (2^n)	$m + 10$

- This also demonstrates the gap between polynomial and exponential algorithms:
 - with an exponential algorithm, fast hardware does not help
 - problem size for exponential algorithms does not scale with faster computers

Big-O relatives

- Big-O (upper bound): $f(n)$ is $O(g(n))$
if $f(n)$ is asymptotically less than or equal to $g(n)$
 $f(n) \leq cg(n)$ for $n > n_0$
- Big-Omega (lower bound): $f(n)$ is $\Omega(g(n))$
if $f(n)$ is asymptotically greater than or equal to $g(n)$
 $f(n) \geq cg(n)$ for $n > n_0$
- Big-Theta (upper/lower bound): $f(n)$ is $\Theta(g(n))$
if $f(n)$ is asymptotically equal to $g(n)$
 $f(n)$ is $O(g(n))$ and $f(n)$ is $\Omega(g(n))$

Summary

- Algorithmic analysis mainly focuses on worst-case asymptotic running times
- Sublinear (e.g., logarithmic), Linear and $n \log n$ algorithms are good
- Polynomial algorithms may be acceptable in many cases
- Exponential algorithms are bad
- We will return to concepts from this lecture while studying various algorithms
- Reading for this lecture: Goodrich, Tamassia, and Goldwasser (2013, chapter 3)
- Next:
 - Common patterns in algorithms
 - Sorting algorithms
 - Reading: Goodrich, Tamassia, and Goldwasser (2013, chapter 12) – up to 12.7

A(another) view of computational complexity

P, NP, NP-complete and all that

- A major division of complexity classes according to Big-O notation is between
 - P polynomial time algorithms
 - NP non-deterministic polynomial time algorithms
- A Big question in computing is whether $P = NP$
- All problems in NP can be reduced in polynomial time to a problem in a subclass of NP (NP-complete)
 - Solving an NP complete problem in P would mean proving

 $P = NP$

Video from <https://www.youtube.com/watch?v=YI40hbAHx3s>

Recurrence relations

the master theorem

- Given a recurrence relation:

$$T(n) = aT\left(\frac{n}{b}\right) + f(n)$$
 - a number of sub-problems
 - b reduction factor or the input
 - $f(n)$ amount of work for creating and combining sub-problems
$$T(n) = \begin{cases} \Theta(n^{\log_b a}) & \text{if } f(n) \text{ is } O(n^{\log_b a - \epsilon}) \\ \Theta(n^{\log_b a} \log n) & \text{if } f(n) \text{ is } \Theta(n^{\log_b a}) \\ \Theta(f(n)) & \text{if } f(n) \text{ is } \Omega(n^{\log_b a + \epsilon}) \text{ and } af(n/b) \leq cf(n) \text{ for some } c < 1 \end{cases}$$
- In many practical cases $a = b$ (simplifies the expressions above)
- But the theorem is not general for all recurrences: it requires equal splits

